

EOS 150 Paramotor engine

EOS 150

— LIGHTWEIGHT & RELIABLE POWER —

- light weight
- simplicity
- short build in length
- smooth quiet running
- low consumption
- fan cooling
- centrifugal clutch
- membrane carburetor
- coil ignition with long life span
- auto decompressor function for easy start-up pull
- reliable
- reasonable price
- made in Austria



technical data and information

engine	one cylinder 2 stroke
displacement	154cc
stroke	52,5mm
bore	61mm
compression ratio	1:10,5
gear ratio of belt drive	1:3,5
carburetor	membrane Walbro WB 37
spark plug	NGK BR9HS
power	25,7HP (18,9KW) at 9000RPM
thrust	>66kg / >70kg 125cm / 130cm prop
starter	rope hand starter / EASY-STARTER
cooling	fan cooling
average consumption	3,3 - 4l/h
fuel inlet	membrane, fiber Reed valve
air inlet	HIFLOW-SHOT air box
fuel recommendation	unleaded 98 Octane
fuel mixture	2%
2-stroke oil	full synthetic
weight (w.o. exhaust)	9,05kg
weight (with exhaust - all complete)	11,4kg
exhaust	Nickel plated
max. build-in length	21cm
dimensions	57x34x25cm
propeller recommendation (rotation anti clockwise) diameters 125cm or 130cm	EOS P&T Carbon 2 blade

- www.eos-engine.com -

